

Technical Data Sheet Durable Metalized Polyester - 704

- General Description:**
- Printed image resists all organic solvents, acids, alkalis
 - Silver high-performance synthetic film
 - Advanced construction requires minimum print head temperatures
 - Good abrasion resistance
 - Good heat and excellent moisture resistance

Uses & Features: Designed for high-performance label applications. Topcoat resists smudging and abrasion when printed with recommended ribbon.
 Provides excellent control of battery parts, asset marking, rating labels and applications requiring harsh environment, solvent and chemical resistance.

Recommended Ribbon: Nortec's Type 181 (i.e. EE01QL181OPJ) TT Ribbon

Thickness:

| | Thickness |
|------------|-----------|
| Substrate: | 2.8 MIL |
| Adhesive: | 1.2 MIL |
| Liner | 3.0 MIL |
| Total: | 7.0 MIL |

Temperatures: Service Temp. Range: -40°F to 302°F (-40°C to 150°C)
 Min. Application Temp: 50°F (10°C)

Shelf Life: 2 years when stored at 70°F (21°C)/50% RH

Warranty: Nortec AMI recommends that a selected label type be thoroughly tested to insure it meets all end user requirements. Nortec AMI warrants only the purchaser that its products are free from defects in material and workmanship. Nortec AMI limits its obligation under this warranty and at its option to repair or replace the product. This warranty is in lieu of any other warranty, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. Nortec AMI is not liable for any damages, including lost profits, lost savings, or other incidental or consequential damages arising out of the use of or inability to use such product.

Rev. 12.09