

Technical Data Sheet Tamper Evident White Vinyl - 741

General Description: A solvent cast PVC film; Matte White Destructible with permanent acrylic adhesive features excellent tack and adhesion on a wide variety of substrates including apolar, slightly rough and curved surfaces. Breaks apart when removal is attempted.

Uses & Features: Suitable for use where product security is an issue. Characterized by combination of low tear strength providing high level of destructibility for tamper evidence. Excellent print resolution and multi-color printing results including wide range of thermal transfer printers. Applications include inventory, food packaging, pharmaceuticals, electronics, hardware and software.

Recommended Ribbons: Nortec 103, 104 or 140 Thermal Transfer Ribbons.

	gsm	Standard	um	Standard
Face	99.5	TAPPI T410	50	TAPPI T411
Adhesive	19			
Liner	74	TAPPI T410	64	TAPPI T411

180° Peel after 24 hours	Value	Unit of Measure	Standard
Steel	Destructs	N/25mm	FTM 1
Glass	Destructs	N/25mm	FTM 1

Temperatures: Service Temp. Range: -20°C to 70°C (-4°F to 158°F).
Min. Application Temp: > 0°C.

Shelf Life: 2 years when stored at 22°C / 50% RH.

Warranty: Nortec AMI recommends that a selected label type be thoroughly tested to insure it meets all end user requirements. Nortec AMI warrants only the purchaser that its products are free from defects in material and workmanship. Nortec AMI limits its obligation under this warranty and at its option to repair or replace the product. This warranty is in lieu of any other warranty, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. Nortec AMI is not liable for any damages, including lost profits, lost savings, or other incidental or consequential damages arising out of the use of or inability to use such product.

Rev. 12.09